

Personnel Key-Fob Tag



Description

The ActiveTag™ product family includes an array of Personnel Tags designed for operation in a variety of applications and environments. The latest addition to the ActiveTag™ line is the key-fob styled Personnel Tag. The tag is 40% smaller than the standard personnel tag and supports replaceable batteries.

A panic alarm feature is available which, at the press of a button, triggers the tag to transmit an alarm signal. A Personnel Beacon Tag is also available that automatically transmits on a preprogrammed timed interval to assist in the location and tracking of personnel across broad areas.

Features

Long Read Range - single lane or wide area coverage up to 35 feet across*

Advanced Communication - dual frequency tag-reader communication enables faster throughput and increases efficiency

Hands-free Operation - safe and convenient; simply drive up and drive through

Functional Linkage™ - link driver to vehicle, tractor to trailer, pallet to forklift, etc.

Duress Option - recessed button manually enables tag transmission when depressed

Serial ID Numbers - factory programmed SIA standard 26-Bit Wiegand I.D. number (custom programming available upon request)

Specifications

Name	ActiveTag™ Personnel Key-Fob Tag
Part Number	AT-132PF-R
Wake-up / Transmit Frequency	126 kHz / 315 MHz
Tag Wake-up Range	Up to 100 feet
Tag Transmit Range	Up to 35 feet*
Operating Life	1 - 3 years**
Operating Temperature	-40°C to +85°C (-40°F to +185°F)
Dimensions	2.8 in x 1.4 in x 0.4 in
Weight (approximate)	0.7 ounce
Options	Ruggedized non-replaceable battery (AT-132RF) Beacon (AT-132PF-RB) Temperature (AT-132PF-RA) Beacon and Temperature (AT-132PF-RBA)

*Operating Range depends on antenna selection, environmental factors and operational requirements. Range in excess of 50 feet is achievable with custom antenna designs. **Operating life will vary depending on beacon rate and duty cycle.